



# I-TRON ZERO

## I-TRON ZERO

### MAIN CHARACTERISTICS

<b>Applications</b>	Street lighting.
<b>Optic</b>	STE-M/S: Asymmetrical optic for suburban street lighting. STU-M/S: Asymmetrical optic for street, urban and cycle-path lighting. STW: Asymmetrical optic for wide urban and suburban road lighting, specific for wet asphalts. SV: Asymmetrical optic for very narrow urban streets or highway entrance/exit turns. S05/S07: Asymmetrical optic for street, urban and green areas lighting. STA: Asymmetrical optic for wide urban road and cycle-path lighting. OP-DX/SX: Asymmetrical optic for crosswalks lighting. Colour temperature: 4000K, 3000K, 2700K, 2200K (others in option)   CRI ≥ 70 LOR= 100%, DLOR= 100%, ULOR= 0% Photobiological safety class: EXEMPT GROUP LED source efficiency: 185 lm/W @ 140mA, Tj=85°C, 4000K
<b>Insulation class</b>	II, I
<b>Protection degree</b>	IP66/IP67   IK09 total
<b>Dimensions</b>	See the drawing
<b>Weight</b>	max 6 kg
<b>Exposed surface</b>	Side: 0.03m <sup>2</sup> – Top: 0.13 m <sup>2</sup>   SCx 0.04 m <sup>2</sup>
<b>Mounting</b>	Bracket / Post-top: Ø33mm ÷ Ø60mm   Ø60mm ÷ Ø76mm(optional)
<b>Tilt Angle</b>	Post-top: -10°/+25° (step 5°)   Bracket: -25°/+10° (step 5°)
<b>LED Modules</b>	Removable / Replaceable.
<b>Gear tray</b>	Tool-free opening of wiring compartment, integrated in the luminaire, separate from the optic unit. Removable wiring. Optional removable wiring plate.
<b>Operating temp.</b>	-40°C / +55°C
<b>Storage temp</b>	-40°C / +80°C
<b>Main reference standards</b>	EN 60598-1, EN 60598-2-3, EN 62471, PD EPRS 003 / EN 62722-2-1 2016, EN 55015, EN 61547, EN 61000-3-2, EN-61000-3-3



### ELECTRICAL CHARACTERISTICS

<b>Rated voltage</b>	220+240V 50/60Hz (Standard tolerance +/-10%, other voltages and tolerances upon request)
<b>Power factor</b>	>0,95 (at full load - F, DA, DAC)
<b>Mains connection</b>	Terminal block for cables max section 4mm <sup>2</sup>
<b>Surge protection</b>	Up to 12kV With SPD: CL.II: 10kV / 10kV CM/DM   CL.I: 12kV / 10kV CM/DM Without SPD: CL.II: 10kV / 6kV CM/DM   CL.I: 10kV / 6kV CM/DM
<b>SPD (optional)</b>	12kV-10kA, type 2+3, with LED signal and thermo fuse to disconnect load at the end of life.
<b>Control system (options)</b>	F: Fixed power not dimmable. DA: Automatic dimming (virtual midnight) with default profile. DAC: Custom DA profile. FLC: Constant light flux. DALI: Digital dimming interface DALI. NEMA: Socket 7 pin (ANSI C136.41). ZHAGA: Socket 4 pin (ZHAGA Book 18).
<b>Optical unit lifetime (Tq=25°C)</b>	>100.000hr L90B10 >100.000hr L90, TM-21

### MATERIALS

<b>Fixing</b>	Die-cast aluminum UNI EN1706 powder painted.
<b>Lower frame</b>	
<b>Upper canopy</b>	
<b>Closure hook</b>	Extruded aluminium with stainless steel spring.
<b>Optic</b>	99.85% aluminum with a surface finish in 99.95% with vacuum-sealed deposition. Aluminum grade class A+ (DIN EN 16268)
<b>Screen</b>	Flat tempered glass, 4mm thickness high transparency.
<b>Cable gland</b>	Plastic M20x1.5 - IP68
<b>Gasket</b>	Polyurethane without joints.
<b>Colour</b>	Graphite - Cod. 01



LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 4000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 4000K, lm)	RATED LED POWER* (Tj=85°C, W)
I-TRON ZERO 5P5 7040.060-1M	STE-M STU-M STW SV	60	1760	11.9	147.8	1847	9.4
I-TRON ZERO 5P5 7040.060-2M			3550	23	154.3	3694	18.8
I-TRON ZERO 5P5 7040.060-3M			5330	33.8	157.6	5541	28.2
I-TRON ZERO 5P5 7040.060-4M			7170	43.4	165.2	7387	37.6
I-TRON ZERO 5P5 7040.100-1M		100	2890	19.1	151.3	3023	16
I-TRON ZERO 5P5 7040.100-2M			5790	37.4	154.8	6046	31.9
I-TRON ZERO 5P5 7040.100-3M			8670	54.8	158.2	9069	47.9
I-TRON ZERO 5P5 7040.100-4M			11550	72	160.4	12092	63.8
I-TRON ZERO 5P5 7040.140-1M		140	4000	26.8	149.2	4150	22.7
I-TRON ZERO 5P5 7040.140-2M			7930	52.3	151.6	8299	45.4
I-TRON ZERO 5P5 7040.140-3M			11860	76.7	154.6	12449	68
I-TRON ZERO 5P5 7040.140-4M			15610	102	153	16598	90.7
I-TRON ZERO 5P5 7040.180-1M		180	5000	34.8	143.6	5227	29.6
I-TRON ZERO 5P5 7040.180-2M			9870	67.7	145.7	10453	59.1
I-TRON ZERO 5P5 7040.180-3M			14750	100	147.5	15680	88.7
I-TRON ZERO 5P5 7040.180-4M			19410	132	147	20906	118
I-TRON ZERO 5P5 7040.060-1M	S05 S07 STA STE-S STU-S	60	1730	11.9	145.3	1847	9.4
I-TRON ZERO 5P5 7040.060-2M			3460	23	150.4	3694	18.8
I-TRON ZERO 5P5 7040.060-3M			5210	33.8	154.1	5541	28.2
I-TRON ZERO 5P5 7040.060-4M			7010	43.4	161.5	7387	37.6
I-TRON ZERO 5P5 7040.100-1M		100	2830	19.1	148.1	3023	16
I-TRON ZERO 5P5 7040.100-2M			5650	37.4	151	6046	31.9
I-TRON ZERO 5P5 7040.100-3M			8480	54.8	154.7	9069	47.9
I-TRON ZERO 5P5 7040.100-4M			11290	72	156.8	12092	63.8
I-TRON ZERO 5P5 7040.140-1M		140	3900	26.8	145.5	4150	22.7
I-TRON ZERO 5P5 7040.140-2M			7760	52.3	148.3	8299	45.4
I-TRON ZERO 5P5 7040.140-3M			11600	76.7	151.2	12449	68
I-TRON ZERO 5P5 7040.140-4M			15260	102	149.6	16598	90.7

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 4000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 4000K, lm)	RATED LED POWER* (Tj=85°C, W)
I-TRON ZERO 5P5 7040.180-1M		180	4870	34.8	139.9	5227	29.6
I-TRON ZERO 5P5 7040.180-2M			9670	67.7	142.8	10453	59.1
I-TRON ZERO 5P5 7040.180-3M			14420	100	144.2	15680	88.7
I-TRON ZERO 5P5 7040.180-4M			18980	132	143.7	20906	118
I-TRON ZERO 5P5 7040.060-1M		60	1710	11.9	143	1847	9.4
I-TRON ZERO 5P5 7040.060-2M			3430	23	149	3694	18.8
I-TRON ZERO 5P5 7040.060-3M			5140	33.8	152	5541	28.2
I-TRON ZERO 5P5 7040.060-4M			6930	43.4	159	7387	37.6
I-TRON ZERO 5P5 7040.100-1M		100	2800	19.1	146	3023	16
I-TRON ZERO 5P5 7040.100-2M			5590	37.4	149	6046	31.9
I-TRON ZERO 5P5 7040.100-3M			8380	54.8	152	9069	47.9
I-TRON ZERO 5P5 7040.100-4M	OP-DX		11160	72	155	12092	63.8
I-TRON ZERO 5P5 7040.140-1M	OP-SX	140	3860	26.8	144	4150	22.7
I-TRON ZERO 5P5 7040.140-2M			7670	52.3	146	8299	45.4
I-TRON ZERO 5P5 7040.140-3M			11470	76.7	149	12449	68
I-TRON ZERO 5P5 7040.140-4M			15090	102	147	16598	90.7
I-TRON ZERO 5P5 7040.180-1M		180	4820	34.8	138	5227	29.6
I-TRON ZERO 5P5 7040.180-2M			9560	67.7	141	10453	59.1
I-TRON ZERO 5P5 7040.180-3M			14260	100	142	15680	88.7
I-TRON ZERO 5P5 7040.180-4M			18760	132	142	20906	118

\*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory.  
 \*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet.  
 Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.  
 Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.  
 Meets Dark Sky requirements when equipped with LEDs with a colour temperature of 3000K or less.  
 The characteristics of the product listed above are subjected to change without notice.

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 3000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 3000K, lm)	RATED LED POWER* (Tj=85°C, W)
I-TRON ZERO 5P5 7030.060-1M	STE-M STU-M STW SV	60	1660	11.9	139.4	1736	9.4
I-TRON ZERO 5P5 7030.060-2M			3340	23	145.2	3472	18.8
I-TRON ZERO 5P5 7030.060-3M			5010	33.8	148.2	5208	28.2
I-TRON ZERO 5P5 7030.060-4M			6740	43.4	155.2	6944	37.6
I-TRON ZERO 5P5 7030.100-1M		100	2720	19.1	142.4	2842	16
I-TRON ZERO 5P5 7030.100-2M			5440	37.4	145.4	5683	31.9
I-TRON ZERO 5P5 7030.100-3M			8150	54.8	148.7	8525	47.9
I-TRON ZERO 5P5 7030.100-4M			10860	72	150.8	11367	63.8
I-TRON ZERO 5P5 7030.140-1M		140	3760	26.8	140.2	3901	22.7
I-TRON ZERO 5P5 7030.140-2M			7450	52.3	142.4	7801	45.4
I-TRON ZERO 5P5 7030.140-3M			11150	76.7	145.3	11702	68
I-TRON ZERO 5P5 7030.140-4M			14670	102	143.8	15602	90.7
I-TRON ZERO 5P5 7030.180-1M		180	4700	34.8	135	4913	29.6
I-TRON ZERO 5P5 7030.180-2M			9280	67.7	137	9826	59.1
I-TRON ZERO 5P5 7030.180-3M			13870	100	138.7	14739	88.7
I-TRON ZERO 5P5 7030.180-4M			18250	132	138.2	19652	118
I-TRON ZERO 5P5 7030.060-1M	S05 S07 STA STE-S STU-S	60	1630	11.9	136.9	1736	9.4
I-TRON ZERO 5P5 7030.060-2M			3260	23	141.7	3472	18.8
I-TRON ZERO 5P5 7030.060-3M			4900	33.8	144.9	5208	28.2
I-TRON ZERO 5P5 7030.060-4M			6590	43.4	151.8	6944	37.6
I-TRON ZERO 5P5 7030.100-1M		100	2660	19.1	139.2	2842	16
I-TRON ZERO 5P5 7030.100-2M			5310	37.4	141.9	5683	31.9
I-TRON ZERO 5P5 7030.100-3M			7970	54.8	145.4	8525	47.9
I-TRON ZERO 5P5 7030.100-4M			10610	72	147.3	11367	63.8
I-TRON ZERO 5P5 7030.140-1M		140	3670	26.8	136.9	3901	22.7
I-TRON ZERO 5P5 7030.140-2M			7290	52.3	139.3	7801	45.4
I-TRON ZERO 5P5 7030.140-3M			10900	76.7	142.1	11702	68
I-TRON ZERO 5P5 7030.140-4M			14340	102	140.5	15602	90.7

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 3000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 3000K, lm)	RATED LED POWER* (Tj=85°C, W)
I-TRON ZERO 5P5 7030.180-1M		180	4580	34.8	131.6	4913	29.6
I-TRON ZERO 5P5 7030.180-2M			9090	67.7	134.2	9826	59.1
I-TRON ZERO 5P5 7030.180-3M			13560	100	135.6	14739	88.7
I-TRON ZERO 5P5 7030.180-4M			17840	132	135.1	19652	118
I-TRON ZERO 5P5 7030.060-1M		60	1610	11.9	135	1736	9.4
I-TRON ZERO 5P5 7030.060-2M			3220	23	140	3472	18.8
I-TRON ZERO 5P5 7030.060-3M			4840	33.8	143	5208	28.2
I-TRON ZERO 5P5 7030.060-4M			6510	43.4	150	6944	37.6
I-TRON ZERO 5P5 7030.100-1M		100	2630	19.1	137	2842	16
I-TRON ZERO 5P5 7030.100-2M			5250	37.4	140	5683	31.9
I-TRON ZERO 5P5 7030.100-3M			7880	54.8	143	8525	47.9
I-TRON ZERO 5P5 7030.100-4M	OP-DX		10490	72	145	11367	63.8
I-TRON ZERO 5P5 7030.140-1M	OP-SX	140	3630	26.8	135	3901	22.7
I-TRON ZERO 5P5 7030.140-2M			7210	52.3	137	7801	45.4
I-TRON ZERO 5P5 7030.140-3M			10780	76.7	140	11702	68
I-TRON ZERO 5P5 7030.140-4M			14180	102	139	15602	90.7
I-TRON ZERO 5P5 7030.180-1M		180	4530	34.8	130	4913	29.6
I-TRON ZERO 5P5 7030.180-2M			8980	67.7	132	9826	59.1
I-TRON ZERO 5P5 7030.180-3M			13410	100	134	14739	88.7
I-TRON ZERO 5P5 7030.180-4M			17640	132	133	19652	118

\*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory.

\*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

Meets Dark Sky requirements when equipped with LEDs with a colour temperature of 3000K or less.

The characteristics of the product listed above are subjected to change without notice.

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 2700K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 2700K, lm)	RATED LED POWER* (Tj=85°C, W)
I-TRON ZERO 5P5 7027.060-1M	STE-M STU-M STW SV	60	1590	11.9	133.6	1662	9.4
I-TRON ZERO 5P5 7027.060-2M			3200	23	139.1	3324	18.8
I-TRON ZERO 5P5 7027.060-3M			4800	33.8	142	4986	28.2
I-TRON ZERO 5P5 7027.060-4M			6450	43.4	148.6	6649	37.6
I-TRON ZERO 5P5 7027.100-1M		100	2600	19.1	136.1	2721	16
I-TRON ZERO 5P5 7027.100-2M			5210	37.4	139.3	5441	31.9
I-TRON ZERO 5P5 7027.100-3M			7800	54.8	142.3	8162	47.9
I-TRON ZERO 5P5 7027.100-4M			10400	72	144.4	10883	63.8
I-TRON ZERO 5P5 7027.140-1M		140	3600	26.8	134.3	3735	22.7
I-TRON ZERO 5P5 7027.140-2M			7140	52.3	136.5	7469	45.4
I-TRON ZERO 5P5 7027.140-3M			10670	76.7	139.1	11204	68
I-TRON ZERO 5P5 7027.140-4M			14050	102	137.7	14938	90.7
I-TRON ZERO 5P5 7027.180-1M		180	4500	34.8	129.3	4704	29.6
I-TRON ZERO 5P5 7027.180-2M			8890	67.7	131.3	9408	59.1
I-TRON ZERO 5P5 7027.180-3M			13280	100	132.8	14112	88.7
I-TRON ZERO 5P5 7027.180-4M			17470	132	132.3	18816	118
I-TRON ZERO 5P5 7027.060-1M	S05 S07 STA STE-S STU-S	60	1560	11.9	131	1662	9.4
I-TRON ZERO 5P5 7027.060-2M			3120	23	135.6	3324	18.8
I-TRON ZERO 5P5 7027.060-3M			4690	33.8	138.7	4986	28.2
I-TRON ZERO 5P5 7027.060-4M			6310	43.4	145.3	6649	37.6
I-TRON ZERO 5P5 7027.100-1M		100	2550	19.1	133.5	2721	16
I-TRON ZERO 5P5 7027.100-2M			5090	37.4	136	5441	31.9
I-TRON ZERO 5P5 7027.100-3M			7630	54.8	139.2	8162	47.9
I-TRON ZERO 5P5 7027.100-4M			10160	72	141.1	10883	63.8
I-TRON ZERO 5P5 7027.140-1M		140	3510	26.8	130.9	3735	22.7
I-TRON ZERO 5P5 7027.140-2M			6980	52.3	133.4	7469	45.4
I-TRON ZERO 5P5 7027.140-3M			10440	76.7	136.1	11204	68
I-TRON ZERO 5P5 7027.140-4M			13730	102	134.6	14938	90.7

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 2700K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 2700K, lm)	RATED LED POWER* (Tj=85°C, W)
I-TRON ZERO 5P5 7027.180-1M			4380	34.8	125.8	4704	29.6
I-TRON ZERO 5P5 7027.180-2M		180	8700	67.7	128.5	9408	59.1
I-TRON ZERO 5P5 7027.180-3M			12980	100	129.8	14112	88.7
I-TRON ZERO 5P5 7027.180-4M			17080	132	129.3	18816	118
I-TRON ZERO 5P5 7027.060-1M			1540	11.9	129	1662	9.4
I-TRON ZERO 5P5 7027.060-2M		60	3080	23	133	3324	18.8
I-TRON ZERO 5P5 7027.060-3M			4630	33.8	136	4986	28.2
I-TRON ZERO 5P5 7027.060-4M			6230	43.4	143	6649	37.6
I-TRON ZERO 5P5 7027.100-1M			2520	19.1	131	2721	16
I-TRON ZERO 5P5 7027.100-2M		100	5030	37.4	134	5441	31.9
I-TRON ZERO 5P5 7027.100-3M			7540	54.8	137	8162	47.9
I-TRON ZERO 5P5 7027.100-4M	OP-DX		10040	72	139	10883	63.8
I-TRON ZERO 5P5 7027.140-1M	OP-SX		3470	26.8	129	3735	22.7
I-TRON ZERO 5P5 7027.140-2M		140	6900	52.3	131	7469	45.4
I-TRON ZERO 5P5 7027.140-3M			10320	76.7	134	11204	68
I-TRON ZERO 5P5 7027.140-4M			13580	102	133	14938	90.7
I-TRON ZERO 5P5 7027.180-1M			4330	34.8	124	4704	29.6
I-TRON ZERO 5P5 7027.180-2M		180	8600	67.7	127	9408	59.1
I-TRON ZERO 5P5 7027.180-3M			12840	100	128	14112	88.7
I-TRON ZERO 5P5 7027.180-4M			16890	132	127	18816	118

\*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory.

\*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

Meets Dark Sky requirements when equipped with LEDs with a colour temperature of 3000K or less.

The characteristics of the product listed above are subjected to change without notice.

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 2200K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 2200K, lm)	RATED LED POWER* (Tj=85°C, W)
I-TRON ZERO 5P5 7022.060-1M	STE-M STU-M STW SV	60	1430	11.9	120.1	1496	9.4
I-TRON ZERO 5P5 7022.060-2M			2880	23	125.2	2992	18.8
I-TRON ZERO 5P5 7022.060-3M			4320	33.8	127.8	4488	28.2
I-TRON ZERO 5P5 7022.060-4M			5810	43.4	133.8	5984	37.6
I-TRON ZERO 5P5 7022.100-1M		100	2340	19.1	122.5	2449	16
I-TRON ZERO 5P5 7022.100-2M			4690	37.4	125.4	4897	31.9
I-TRON ZERO 5P5 7022.100-3M			7020	54.8	128.1	7346	47.9
I-TRON ZERO 5P5 7022.100-4M			9360	72	130	9795	63.8
I-TRON ZERO 5P5 7022.140-1M		140	3240	26.8	120.8	3361	22.7
I-TRON ZERO 5P5 7022.140-2M			6420	52.3	122.7	6722	45.4
I-TRON ZERO 5P5 7022.140-3M			9610	76.7	125.2	10083	68
I-TRON ZERO 5P5 7022.140-4M			12640	102	123.9	13445	90.7
I-TRON ZERO 5P5 7022.180-1M		180	4050	34.8	116.3	4233	29.6
I-TRON ZERO 5P5 7022.180-2M			8000	67.7	118.1	8467	59.1
I-TRON ZERO 5P5 7022.180-3M			11950	100	119.5	12700	88.7
I-TRON ZERO 5P5 7022.180-4M			15730	132	119.1	16934	118
I-TRON ZERO 5P5 7022.060-1M	S05 S07 STA STE-S STU-S	60	1400	11.9	117.6	1496	9.4
I-TRON ZERO 5P5 7022.060-2M			2810	23	122.1	2992	18.8
I-TRON ZERO 5P5 7022.060-3M			4220	33.8	124.8	4488	28.2
I-TRON ZERO 5P5 7022.060-4M			5680	43.4	130.8	5984	37.6
I-TRON ZERO 5P5 7022.100-1M		100	2290	19.1	119.8	2449	16
I-TRON ZERO 5P5 7022.100-2M			4580	37.4	122.4	4897	31.9
I-TRON ZERO 5P5 7022.100-3M			6870	54.8	125.3	7346	47.9
I-TRON ZERO 5P5 7022.100-4M			9140	72	126.9	9795	63.8
I-TRON ZERO 5P5 7022.140-1M		140	3160	26.8	117.9	3361	22.7
I-TRON ZERO 5P5 7022.140-2M			6290	52.3	120.2	6722	45.4
I-TRON ZERO 5P5 7022.140-3M			9400	76.7	122.5	10083	68
I-TRON ZERO 5P5 7022.140-4M			12360	102	121.1	13445	90.7



LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 2200K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 2200K, lm)	RATED LED POWER* (Tj=85°C, W)
I-TRON ZERO 5P5 7022.180-1M			3940	34.8	113.2	4233	29.6
I-TRON ZERO 5P5 7022.180-2M		180	7830	67.7	115.6	8467	59.1
I-TRON ZERO 5P5 7022.180-3M			11680	100	116.8	12700	88.7
I-TRON ZERO 5P5 7022.180-4M			15370	132	116.4	16934	118
I-TRON ZERO 5P5 7022.060-1M		60	1390	11.9	116	1496	9.4
I-TRON ZERO 5P5 7022.060-2M			2780	23	120	2992	18.8
I-TRON ZERO 5P5 7022.060-3M			4170	33.8	123	4488	28.2
I-TRON ZERO 5P5 7022.060-4M			5610	43.4	129	5984	37.6
I-TRON ZERO 5P5 7022.100-1M		100	2270	19.1	118	2449	16
I-TRON ZERO 5P5 7022.100-2M			4530	37.4	121	4897	31.9
I-TRON ZERO 5P5 7022.100-3M			6790	54.8	123	7346	47.9
I-TRON ZERO 5P5 7022.100-4M	OP-DX		9040	72	125	9795	63.8
I-TRON ZERO 5P5 7022.140-1M	OP-SX	140	3130	26.8	116	3361	22.7
I-TRON ZERO 5P5 7022.140-2M			6210	52.3	118	6722	45.4
I-TRON ZERO 5P5 7022.140-3M			9290	76.7	121	10083	68
I-TRON ZERO 5P5 7022.140-4M			12220	102	119	13445	90.7
I-TRON ZERO 5P5 7022.180-1M		180	3900	34.8	112	4233	29.6
I-TRON ZERO 5P5 7022.180-2M			7740	67.7	114	8467	59.1
I-TRON ZERO 5P5 7022.180-3M			11550	100	115	12700	88.7
I-TRON ZERO 5P5 7022.180-4M			15200	132	115	16934	118

\*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory.

\*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance:  $\pm 7\%$ . Power tolerance:  $\pm 7\%$ .

Power tolerance with ZHAGA version or power supply D4i/SR:  $\pm 10\%$ .

Meets Dark Sky requirements when equipped with LEDs with a colour temperature of 3000K or less.

The characteristics of the product listed above are subjected to change without notice.